

Caratteristiche tecniche

AerWay®

MODELLI	AW45-SH-3P	AW60-SH-3P	AW45-SH-T	AW60-SH-T
PORTATO/ TRAINATO	PORTATO	PORTATO	TRAINATO	TRAINATO
LARGHEZZA DI LAVORO	110 cm	145 cm	110 cm	145 cm
PESO ZAVORRA	295 kg	390 kg	295 kg	390 kg
PESO ATTREZZO	442 kg	518 kg	540 kg	603 kg



Rotori

SHATTER	AW45-SH-3P	AW60-SH-3P	AW45-SH-T	AW60-SH-T
NUMERO LAME	24	32	24	32
PROFONDITÀ	18 cm	18 cm	18 cm	18 cm
DISTANZA TRA LAME	19 cm	19 cm	19 cm	19 cm
PESO	95 kg	129 kg	95 kg	129 kg

SPORT	AW45-SH-3P	AW60-SH-3P	AW45-SH-3T	AW60-SH-3T
NUMERO LAME	32	44	32	44
PROFONDITÀ	15 cm	15 cm	15 cm	15 cm
DISTANZA TRA LAME	12,7 cm	12,7 cm	12,7 cm	12,7 cm
PESO	90 kg	128 kg	90 kg	128 kg

SOTTILI	AW45-SH-3P	AW60-SH-3P	AW45-SH-3T	AW60-SH-3T
NUMERO LAME	32	44	32	44
PROFONDITÀ	15 cm	15 cm	15 cm	15 cm
DISTANZA TRA LAME	12,7 cm	12,7 cm	12,7 cm	12,7 cm
PESO	80 kg	108 kg	80 kg	108 kg

MULTIDENTI	AW45-SH-3P	AW60-SH-3P	AW45-SH-T	AW60-SH-T
NUMERO LAME	13	18	13	18
PROFONDITÀ	5 cm	5 cm	5 cm	5 cm
DISTANZA TRA LAME	8 cm	8 cm	8 cm	8 cm
PESO	100 kg	136 kg	100 kg	136 kg

CAROTATORE	AW45-SH-3P	AW60-SH-3P	AW45-SH-3T	AW60-SH-3T
NUMERO FUSTELLE	60	84	60	84
PROFONDITÀ DI LAVORO	10 cm	10 cm	10 cm	10 cm
DIAMETRO FUSTELLA	19 mm	19 mm	19 mm	19 mm
DISTANZA TRA FORI	10 cm	10 cm	10 cm	10 cm
PESO	50 kg	60 kg	50 kg	60 kg

